





15 - 250kw, electric or diesel driven

cold or hot water, in compact chassis

base jet chassis „S“

**base jet 15-d**  
 ■ 15 kW, 500 bar, 15 l/min

**base jet 30-e**  
 ■ 30 kW, 500 bar, 30 l/min  
 ■ 30 kW, 1000 bar, 16 l/min

**base jet 15-e**  
 ■ 15 kW, 300 bar, 30 l/min, 70 °C  
 ■ 15 kW, 500 bar, 16 l/min, 95 °C

500 bar 30 m  
 1000 bar 20 m

base jet chassis „M“

**base jet 30-d**  
 ■ 30 kW, 300 bar, 50 l/min  
 ■ 30 kW, 500 bar, 30 l/min  
 ■ 30 kW, 1000 bar, 16 l/min  
 ■ 30 kW, 2000 bar, 8 l/min

300 / 500 bar 30 m  
 1000 / 2000 bar 20 m

base jet chassis „L“

**base jet 30-d**  
 ■ 30 kW, 500 bar, 30 l/min, 95 °C

**base jet 125-d**  
 ■ 125 kW, 1000 bar, 60 l/min  
 ■ 125 kW, 1500 bar, 38 l/min  
 ■ 125 kW, 2500 bar, 24 l/min  
 ■ 125 kW, 3000 bar, 20 l/min

**base jet 125-e**  
 ■ 125 kW, 1000 bar, 67 l/min  
 ■ 125 kW, 2500 bar, 26 l/min  
 ■ 125 kW, 3000 bar, 22 l/min

1000 bar 20 m  
 2500 / 3000 bar 20 m

base jet chassis „XL“

**base jet 250-d**  
 ■ 250 kW, 1000 bar, 129 l/min  
 ■ 250 kW, 1500 bar, 82 l/min  
 ■ 250 kW, 3000 bar, 41 l/min

**base jet 250-e**  
 ■ 250 kW, 1000 bar, 141 l/min  
 ■ 250 kW, 1500 bar, 90 l/min  
 ■ 250 kW, 3000 bar, 45 l/min

